

Compression Lever Latch

6-160.01



Advantages

- Flat compression lever latch with release button.
- With pre-assembled mounting bracket.
- No rear access needed for assembly.
- In closed position the lever latch cannot be disassembled.
- Vibration-proof according to DIN EN 61373.
- Adjustment of the H-dimension (1.) from 0 to 40mm.
- Lockable lever latches with stainless dust cover and 2 keys.
- The spring bolt keeps doors and flaps always under tension against the frame.
- No need for readjusting if the pressure if the sealing decreases.

Material

- **Compression lever latch:** zinc die, black, powder coated
- **Clamp:** steel, zinc plated
- **Spring bolt and spring:** stainless steel

Remarks

(S) Door-thickness max. 3.2mm

Installation:

2. the complete latch can be installed in the cutout from the front.
3. by turning the screw (PH2) from the outside, the mounting bracket spreads and fixes the latch in the door panel.
4. the latch is securely fastened by the mounting backet in the cutout.
5. by closing the latch the door is pulled against the frame.



Compression Lever Latch, without lock

	Product number	variable H-dimension	Installation type	Delivery Unit
a)	282-9413.00-00003	0 mm - 6 mm	screw-on	1 pc.
b)	282-9413.00-00009	6 mm - 12 mm	screw-on	1 pc.
c)	282-9413.00-00015	12 mm - 18 mm	screw-on	1 pc.
d)	282-9413.00-00020	18 mm - 22 mm	screw-on	1 pc.
e)	282-9413.00-00025	22 mm - 28 mm	screw-on	1 pc.
f)	282-9413.00-00031	28 mm - 34 mm	screw-on	1 pc.

	Product number	variable H-dimension	Installation type	Delivery Unit
g)	282-9413.00-00037	34 mm - 40 mm	screw-on	1 pc.

Compression Lever Latch, lockable

	Product number	variable H-dimension	Latching type	Installation type	Delivery Unit
a)	282-9414.00-00003	0 mm - 6 mm	keyed alike DIRAK 1333	screw-on	1 pc.
a)	282-9415.00-00003	0 mm - 6 mm	keyed different	screw-on	1 pc.
b)	282-9414.00-00009	6 mm - 12 mm	keyed alike DIRAK 1333	screw-on	1 pc.
b)	282-9415.00-00009	6 mm - 12 mm	keyed different	screw-on	1 pc.
c)	282-9414.00-00015	12 mm - 18 mm	keyed alike DIRAK 1333	screw-on	1 pc.
c)	282-9415.00-00015	12 mm - 18 mm	keyed different	screw-on	1 pc.
d)	282-9414.00-00020	18 mm - 22 mm	keyed alike DIRAK 1333	screw-on	1 pc.
d)	282-9415.00-00020	18 mm - 22 mm	keyed different	screw-on	1 pc.
e)	282-9414.00-00025	22 mm - 28 mm	keyed alike DIRAK 1333	screw-on	1 pc.
e)	282-9415.00-00025	22 mm - 28 mm	keyed different	screw-on	1 pc.
f)	282-9414.00-00031	28 mm - 34 mm	keyed alike DIRAK 1333	screw-on	1 pc.
f)	282-9415.00-00031	28 mm - 34 mm	keyed different	screw-on	1 pc.
g)	282-9414.00-00037	34 mm - 40 mm	keyed alike DIRAK 1333	screw-on	1 pc.
g)	282-9415.00-00037	34 mm - 40 mm	keyed different	screw-on	1 pc.

