

# DST Quarter-Turn TRENTA Pr30 L18

1-082DST



## Advantages

- Flush quarter-turn for cutout 30x30mm.
- Rectangular cutout guarantees a perfect alignment.
- IP65 according to DIN EN 60529 by sealing kit (optional).
- RH / LH application.
- Grounding by grounding clip (optional).
- Available pre-assembled on request.
- The quarter-turn can be snapped-in as a completely pre-assembled unit.
- Installation tool-less and vibration-proof.
- Blind installation in closed profiles.

## Material

- **Housing:** zinc die, black
- **Snap wedges:** sintered steel
- **Clip:** spring steel

## Remarks

**Attention:** H-dimension not less than 14mm!

Please configure the quarter-turn with insert and cam.

1. the cutouts can be provided with an indentation to avoid errors.

## Quarter-Turn TRENTA

	Product number	Quantity SNAP wedges	Clamping range (S)	Installation type	Delivery Unit
a)	406-9001.00-00015	4, for H.D. applications	0.8 mm - 1.5 mm	tool-less	10 pcs.
a)	406-9001.00-00020	4, for H.D. applications	1.3 mm - 2 mm	tool-less	10 pcs.
a)	406-9001.00-00022	4, for H.D. applications	1.5 mm - 2.2 mm	tool-less	10 pcs.
b)	406-9002.00-00015	2, for light applications	0.8 mm - 1.5 mm	tool-less	10 pcs.
b)	406-9002.00-00020	2, for light applications	1.3 mm - 2 mm	tool-less	10 pcs.

---

	Product number	Quantity SNAP wedges	Clamping range (S)	Installation type	Delivery Unit
b)	406-9002.00-00022	2, for light applications	1.5 mm - 2.2 mm	tool-less	10 pcs.

---

