

DST Quarter-Turn Pr32x20 L18 with FIAT Insert

1-086DST



Advantages

- Flush quarter-turn for cutout 32x20mm.
- Rectangular cutout guarantees a perfect alignment.
- Operation not possible without an appropriate key.
- The key is removable in 90° steps.
- IP65 according to DIN EN 60529.
- RH / LH application.
- Grounding by grounding clip (optional).
- The quarter-turn can be snapped-in as a completely pre-assembled unit.
- Installation tool-less and vibration-proof.
- Blind installation in closed profiles.

Material

- **Housing, insert and escutcheon:** zinc die, chrome plated
- **Snap wedges:** sintered steel
- **O-ring:** NBR, black
- **Serrated screw:** steel, zinc plated

Remarks

ATTENTION: H-dimension of the cam not less than 12mm

Completely pre-assembled **without** cam.

1. escutcheon
2. o-ring

Quarter-turn with FIAT insert

| | Product number | Clamping range (S) | Installation type | Delivery Unit |
|----|-------------------|--------------------|-------------------|---------------|
| a) | 455-9003.00-00013 | 1 mm - 1.7 mm | tool-less | 10 pcs. |
| a) | 455-9003.00-00018 | 1.5 mm - 2.2 mm | tool-less | 10 pcs. |
| a) | 455-9003.00-00026 | 2.3 mm - 3 mm | tool-less | 10 pcs. |

