

Quarter-Turn with Mask Pr20.1 L18/L30/L36

1-087



Advantages

- For cutout Pr20.1.
- The quarter-turn can only be operated with a special matching male key (sub e).
- The operation of this quarter-turn with standard male square keys without a special groove is not possible.
- IP65 according to DIN EN 60529.
- RH / LH application.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.

Material

a) and b)

- **Housing, insert and mask:** zinc die, chrome plated
- **Nut:** steel, zinc plated

c)

- **Housing and insert:** steel, chrome plated
- **Mask:** zinc die, chrome plated
- **Grounding nut:** zinc die, untreated
- **Wave washer and serrated screw:** steel, zinc plated
- **O-ring and flat external seal:** NBR

Remarks

Completely pre-assembled **without** cam.

Negatively bent cams can not be installed pre-assembled.

1. flat external seal
2. nut
3. grounding nut

Quarter-Turn with mask and socket square 7.6mm insert

	Product number	Housing length	Door-thickness (S)	Grounding type	Installation type	Delivery Unit
a)	255-8006.00-00000	18 mm	0 mm - 8 mm	-	screw-on	10 pcs.
b)	255-8008.00-00000	30 mm	0 mm - 20 mm	Grounding nut	screw-on	10 pcs.
c)	255-8022.00-00036	36 mm	0 mm - 26 mm	Grounding nut	screw-on	10 pcs.

