

Quarter-Turn 2K Polyamide Pr20.1 L18

1-092



Advantages

- For cutout Pr20.1.
- Protective insulated.
- With moulded-in, captive TPE seal (under the head and inside the housing).
- IP65/67 according to DIN EN 60529.
- IP69K according to DIN 40050.
- RH / LH application.
- Insert and cam can be clipped together without tools before the installation in the housing.
- A pre-assembled quarter-turn can be installed through the cutout.

Material

- **Housing, nut, insert and cam:** PA6, black
- **Seal:** TPE, red

Remarks

(S) Door-thickness max. 8mm.

Please configure the quarter-turn with nut, insert and cam.

Quarter-Turn housing 2K

	Product number	Name	Housing length	Captive seal	Installation type	Delivery Unit
a)	200-0211.07-07701	Quarter-Turn	18 mm	Yes	screw-on	50 pcs.
a1)	203-0901.03-00000	Nut	-	-	screw-on	50 pcs.

Insert 2K

	Product number	Insert	Delivery Unit
b1)	100-0388.50-07705	Double bit 3mm pin	50 pcs.

	Product number	Insert	Delivery Unit
b2)	100-0388.50-07701	Double bit 5mm pin	50 pcs.
b3)	100-0388.50-07702	Square 8mm	50 pcs.
b4)	100-0388.50-07703	Triangular 8mm	50 pcs.
b5)	100-0388.50-07707	Wing knob	50 pcs.
b6)	100-0388.50-07704	Slotted 2x4mm	50 pcs.

Cams 2K, L45, with stop

	Product number	H-dimension	Delivery Unit
c)	200-0769.50-07718	18 mm	50 pcs.
c)	200-0769.50-07720	20 mm	50 pcs.
c)	200-0769.50-07722	22 mm	50 pcs.
c)	200-0769.50-07724	24 mm	50 pcs.
c)	200-0769.50-07728	28 mm	50 pcs.

