

Quarter-Turn Pr20.1 L18

1-100.01



Advantages

- Flush quarter-turn for cutout Pr20.1.
- IP65/67 according to DIN EN 60529 (optional).
- RH / LH application.
- Grounding by grounding clip or grounding nut.
- On request parts can be assembled.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.

Material

- **Housing:** zinc die, chrome plated or black
- **Nut:** steel, zinc plated
- **Grounding nut:** zinc die, untreated
- **Grounding clip:** stainless steel

Remarks

(S) Door-thickness max. 8mm

Please configure the quarter-turn with insert and cam.

1. nut
2. grounding nut
3. grounding clip

Quarter-Turn housing, zinc die Ø32

	Product number	Surface	Grounding type	Installation type	Delivery Unit
a)	100-9053.00-00000	chrome plated	-	screw-on	10 pcs.
a)	100-9054.00-00000	chrome plated	Grounding nut	screw-on	10 pcs.
a)	100-9055.00-00000	chrome plated	Grounding clip	screw-on	10 pcs.
a)	100-9056.00-00000	black	-	screw-on	10 pcs.



	Product number	Surface	Grounding type	Installation type	Delivery Unit
a)	100-9057.00-00000	black	Grounding nut	screw-on	10 pcs.
a)	100-9058.00-00000	black	Grounding clip	screw-on	10 pcs.

