

Quarter-Turn Pr20.1 L36

1-110.01



Advantages

- Flat Quarter-turn for cutout Pr20.1.
- IP65/67 according to DIN EN 60529 by sealing kit (optional).
- RH / LH application.
- Grounding by grounding nut.
- On request parts can be assembled.
- The Quarter-turn can be screwed into the cutout with the pre-assembled cam.

Material

- **Housing:** zinc die, matte chrome plated, glossy chrome plated or black
- **Nut:** steel, zinc plated
- **Grounding nut:** zinc die, untreated

Remarks

Door-thickness (S) max. 26mm

Please configure the Quarter-turn with insert (adapter) and cam.

Quarter-Turn housing

	Product number	Surface	Grounding type	Installation type	Delivery Unit
a)	100-9065.40-00036	matte chrome plated		screw-on	10 pcs.
a)	100-9065.31-00036	glossy chrome plated		screw-on	10 pcs.
a)	100-9065.00-00000	black		screw-on	10 pcs.
a)	100-9070.00-00036	matte chrome plated	Grounding nut	screw-on	10 pcs.
a)	100-9068.00-00036	glossy chrome plated	Grounding nut	screw-on	10 pcs.
a)	100-9066.00-00036	black	Grounding nut	screw-on	10 pcs.

