

Cylinder Quarter-Turn Pr20.1 L18

1-120



Advantages

- For cutout Pr20.1.
- IP65 according to DIN EN 60529 by dust cap 200-4101 (optional).
- IP65/IP67 according to DIN EN 60529 by dust cap 200-4103 (optional).
- RH / LH application.
- Grounding by grounding nut.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.
- 2 keys included.
- With stainless steel cylinder cover and dust-shutter.

Material

- **Housing:** zinc die, chrome plated or black
- **Grounding nut:** zinc die, untreated

Remarks

(S) Door-thickness max. 8mm

Completely pre-assembled **without** cam.

Maximum load for the key 4Nm.

Cylinder quarter-turn, zinc die

Product number	Head diameter	Latching type	Surface	Installation type	Delivery Unit
a) 200-9201.00-00000	Ø28	keyed alike DIRAK 1333	chrome plated	screw-on	1 pc.
a) 500-9201.00-00000	Ø28	keyed alike DS200	chrome plated	screw-on	1 pc.
a) 200-9203.00-00000	Ø28	keyed different	chrome plated	screw-on	1 pc.
a) 200-9202.00-00000	Ø28	keyed alike DIRAK 1333	black	screw-on	1 pc.
a) 500-9202.00-00000	Ø28	keyed alike DS200	black	screw-on	1 pc.
a) 200-9204.00-00000	Ø28	keyed different	black	screw-on	1 pc.

	Product number	Head diameter	Latching type	Surface	Installation type	Delivery Unit
a)	200-9205.00-00000	Ø32	keyed alike DIRAK 1333	chrome plated	screw-on	1 pc.
a)	500-9205.00-00000	Ø32	keyed alike DS200	chrome plated	screw-on	1 pc.
a)	200-9207.00-00000	Ø32	keyed different	chrome plated	screw-on	1 pc.
a)	200-9206.00-00000	Ø32	keyed alike DIRAK 1333	black	screw-on	1 pc.
a)	500-9206.00-00000	Ø32	keyed alike DS200	black	screw-on	1 pc.
a)	200-9208.00-00000	Ø32	keyed different	black	screw-on	1 pc.

