

# DST Cylinder Quarter-Turn Pr32x20 L22

1-120DST



## Advantages

- Flush quarter-turn for cutout 32x20mm.
- Rectangular cutout guarantees a perfect alignment.
- The rotatable bottom can be positioned in any 90° position, making the bit of the key always pointing in the same direction for both RH and LH doors.
- RH / LH application.
- The quarter-turn can be snapped-in as a completely pre-assembled unit.
- Installation tool-less and vibration-proof.
- Blind installation in closed profiles.
- 2 keys included.
- With stainless cylinder cover and dust-shutter.

## Material

- **Housing and cylinder:** zinc die, chrome plated
- **Snap wedges:** sintered steel
- **Loose bottom:** zinc die, zinc plated
- **Serrated screw:** steel, zinc plated
- **O-ring:** NBR, black, serves as security for the snap wedges

## Remarks

H-dimension of the cam  $L=35 \geq 12\text{mm}$

H-dimension of the cam  $L=45 \geq 6\text{mm}$

Completely pre-assembled **without** cam.

Maximum load for the key 4Nm.

Grounding by grounding clip 200-1103.04.00000 on request.

1. rotatable bottom

## Cylinder Quarter-Turn, zinc die

	Product number	Clamping range (S)	Latching type	Surface	Installation type	Delivery Unit
a)	406-9007.00-00013	1 mm - 1.7 mm	keyed alike DIRAK 1333	chrome plated	tool-less	1 pc.
a)	406-9007.00-00018	1.5 mm - 2.2 mm	keyed alike DIRAK 1333	chrome plated	tool-less	1 pc.
a)	406-9007.00-00026	2.3 mm - 3 mm	keyed alike DIRAK 1333	chrome plated	tool-less	1 pc.
b)	406-9008.00-00013	1 mm - 1.7 mm	keyed different	chrome plated	tool-less	1 pc.
b)	406-9008.00-00018	1.5 mm - 2.2 mm	keyed different	chrome plated	tool-less	1 pc.

---

	<b>Product number</b>	<b>Clamping range (S)</b>	<b>Latching type</b>	<b>Surface</b>	<b>Installation type</b>	<b>Delivery Unit</b>
b)	406-9008.00-00026	2.3 mm - 3 mm	keyed different	chrome plated	tool-less	1 pc.
a)	406-9009.00-00013	1 mm - 1.7 mm	keyed alike DIRAK 1333	black	tool-less	1 pc.
a)	406-9009.00-00018	1.5 mm - 2.2 mm	keyed alike DIRAK 1333	black	tool-less	1 pc.
b)	406-9010.00-00013	1 mm - 1.7 mm	keyed different	black	tool-less	1 pc.
b)	406-9010.00-00018	1.5 mm - 2.2 mm	keyed different	black	tool-less	1 pc.
b)	406-9010.00-00026	2.3 mm - 3 mm	keyed different	black	tool-less	1 pc.

---

