

# Cylinder Quarter-Turn Polyamide Pr20.1 L18

1-121



## Advantages

- For cutout Pr20.1.
- Protective insulated and vibration-proof.
- IP65 according to DIN EN 60529 by dust cap 200-4101 (optional).
- IP65/67 according to DIN EN 60529 by dust cap 200-4103 (optional).
- RH / LH application.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.
- 2 keys included in scope of delivery.

## Material

- **Housing:** PA, black
- **Nut:** PA, black, steel, zinc plated or stainless steel

## Remarks

(S) Door-thickness max. 8mm

Completely pre-assembled **without** cam.

Slide shoe and MLA door contact only in conjunction with cams 1-102.

## Quarter-turn, PA

	Product number	Latching type	Surface nut	Installation type	Delivery Unit
a)	200-9210.00-00000	keyed alike DIRAK 1333	black	screw-on	1 pc.
a)	200-9211.00-00000	keyed alike DIRAK 1333	zinc plated	screw-on	1 pc.
a)	200-9212.00-00000	keyed alike DIRAK 1333	stainless steel	screw-on	1 pc.
a)	200-9213.00-00000	keyed different	black	screw-on	1 pc.
a)	200-9214.00-00000	keyed different	zinc plated	screw-on	1 pc.



---

	<b>Product number</b>	<b>Latching type</b>	<b>Surface nut</b>	<b>Installation type</b>	<b>Delivery Unit</b>
a)	200-9215.00-00000	keyed different	stainless steel	screw-on	1 pc.

---

