

Quarter-Turn with Wing Knob Pr20.1 L18

1-130



Advantages

- For cutout Pr20.1.
- With and without cylinder.
- Version **without** cylinder IP65 according to DIN EN 60529.
- RH / LH application.
- Grounding by grounding nut.
- On request parts can be assembled.
- A pre-assembled quarter-turn can be installed in the cutout.

Material

Version a) and b)

- **Housing:** zinc die, black
- **Cylinder:** zinc die with stainless steel dust-shutter
- **Wing knob:** PA, black with zinc die core
- **Plug:** PA, black
- **Grounding nut:** zinc die

Version a1) and b1)

- **Housing, cylinder, wing knob and plug:** PA, black
- **Nut:** zinc die or PA

Remarks

(S) Door-thickness max. 8mm

1. nut
2. grounding nut

Please configure the quarter-turn with a cam.

Quarter-Turn L18 with wing knob

	Product number	Latching type	Material	Surface nut	Grounding type	IP protection	Installation type	Delivery Unit
a)	200-9301.00-00000	-	PA / zinc die core	untreated	Grounding nut	IP65	screw-on	1 pc.
a1)	200-9368.00-00000	-	PA	zinc plated	-	IP65	screw-on	1 pc.
a1)	200-9371.00-00000	-	PA	black	-	IP65	screw-on	1 pc.
b)	200-9302.00-00000	keyed alike DIRAK 1333	PA / zinc die core	untreated	Grounding nut		screw-on	1 pc.
b1)	200-9369.00-00000	keyed alike DIRAK 1333	PA	zinc plated	-		screw-on	1 pc.
b1)	200-9372.00-00000	keyed alike DIRAK 1333	PA	black	-		screw-on	1 pc.
b)	500-9302.00-00000	keyed alike DS200	PA / zinc die core	untreated	Grounding nut		screw-on	1 pc.
b)	200-9303.00-00000	keyed different	PA / zinc die core	untreated	Grounding nut		screw-on	1 pc.
b1)	200-9370.00-00000	keyed different	PA	zinc plated	-		screw-on	1 pc.
b1)	200-9373.00-00000	keyed different	PA	black	-		screw-on	1 pc.

