

Quarter-Turn Pr20.1 L18/40 for Padlock

1-132



Advantages

- For cutout 20.1.
- IP66 according to DIN EN 60529.
- RH / LH application
- Grounding by grounding nut.
- A pre-assembled quarter-turn can be installed in the cutout.

Material

- **Wing knob:** zinc die, chrome plated or black
- **Housing:** zinc die, zinc plated
- **Grounding nut:** zinc die

Remarks

(S) Door-thickness see table

Please configure the quarter-turn with a cam.
Padlock feature only if cam is at 90° to the wing knob.

1. seal

Quarter-Turn, zinc die, for padlock

Product number	Surface	Version	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a) 200-9365.00-00000	black	Smooth coating	18 mm	0 mm - 8 mm	screw-on	1 pc.
a) 100-9311.00-00000	black	Smooth coating	40 mm	0 mm - 30 mm	screw-on	1 pc.
a) 200-9365.TX-00000	black	Textured coating	18 mm	0 mm - 8 mm	screw-on	1 pc.
a) 100-9311.TX-00000	black	Textured coating	40 mm	0 mm - 30 mm	screw-on	1 pc.
a) 200-9364.00-00000	chrome plated	-	18 mm	0 mm - 8 mm	screw-on	1 pc.
a) 100-9310.00-00000	chrome plated	-	40 mm	0 mm - 30 mm	screw-on	1 pc.

