

Quarter-Turn with Drip Handle Pr20.1 L18

1-135



Advantages

- Versions **without cylinder** are water and dust tight according to IP65 DIN EN 60529.
- Versions **with cylinder** are water and dust tight according to IP54 DIN EN 60529.
- RH / LH application.
- Grounding by grounding nut.
- On request parts can be assembled.
- A pre-assembled quarter-turn can be installed in the cutout.

Material

- **Drip handle:** PA, black with zinc die core
- **Housing:** zinc die, chrome plated
- **Cylinder:** PA, black or zinc die, chrome plated
- **Plug:** PA, black
- **Grounding nut:** zinc die

Remarks

(S) Door-thickness max. 8mm

Please configure the quarter-turn with a cam.

1. seal
2. plug

Quarter-Turn with drip handle

	Product number	Version	Latching type	Material cylinder	Surface cylinder	IP protection	Installation type	Delivery Unit
a)	200-9394.00-00000	Blind plug	-			IP65	screw-on	1 pc.
b)	200-9392.00-00000	cylinder	keyed alike DIRAK 1333	PA	black	IP54	screw-on	1 pc.
b)	200-9393.00-00000	cylinder	keyed different	PA	black	IP54	screw-on	1 pc.

	Product number	Version	Latching type	Material cylinder	Surface cylinder	IP protection	Installation type	Delivery Unit
b)	200-9395.00-00000	cylinder	keyed alike DIRAK 1333	zinc die	chrome plated	IP54	screw-on	1 pc.
b)	200-9396.00-00000	cylinder	keyed different	zinc die	chrome plated	IP54	screw-on	1 pc.
b)	500-9395.00-00000	cylinder	keyed alike DS200	zinc die	chrome plated	IP54	screw-on	1 pc.

