

Quarter-Turn with L-Handle Pr20.1 L18

1-151



Advantages

- The radial spring loaded insert automatically locks the handle when the handle rotates back into the closed position.
- RH / LH application.
- Grounding by grounding nut.
- On request parts can be assembled by DIRAK.
- A pre-assembled quarter-turn can be installed in the cutout.

Material

- **L-handle:** PA, black with zinc die core
- **Insert:** zinc die, chrome plated
- **Grounding nut:** zinc die

Remarks

(S) Door-thickness max. 8mm

Please configure the quarter-turn with a cam.

Padlock feature only if cam is at 90° to the L-handle.

Quarter-Turn with L-handle

	Product number	Insert	Installation type	Delivery Unit
a)	200-9429.00-00000	Square 6mm	screw-on	1 pc.
b)	200-9431.00-00000	Square 8mm	screw-on	1 pc.
c)	200-9432.00-00000	Double bit 3mm pin	screw-on	1 pc.
d)	200-9433.00-00000	Double bit 5mm pin	screw-on	1 pc.
e)	200-9435.00-00000	Triangular 8mm	screw-on	1 pc.
f)	200-9436.00-00000	Slotted 2x4mm	screw-on	1 pc.
g)	200-9475.00-00000	Slotted recessed coinproof	screw-on	1 pc.

