

Safety Quarter-Turn Pr20.1 L18 Stainless Steel

7-075



Advantages

- Safety quarter-turn, vibration-proof also at high sealing pressure through an integrated latch.
- Completely closed surface.
- Closing rotation 90°.
- Fire protection tested with E60 classification according to DIN EN 45545-3.
- IP65 according to DIN EN 60529. (included in scope of delivery)
- RH / LH application.
- Grounding by single-sided grounding nut.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.
- Operation not possible without an appropriate key (only keys form A, B, C or D of 6-100).
- The double bit key is captive in open position, pull-off force max. 300N

Material

- **Housing, insert, escutcheon and spring loaded link:** AISI 316
- **Pin:** AISI 303
- **O-ring:** NBR

Remarks

(S) Door-thickness max. 8mm

Completely pre-assembled **without** cam.

1. escutcheon
2. spring loaded link
3. flush, closed surface
4. position cam in the direction of marking

Safety quarter-turn with insert

	Product number	Version	Insert	Installation type	Delivery Unit
a)	255-9429.00-00000	RH version	Double bit 3mm pin	screw-on	1 pc.
a)	255-9430.00-00000	LH version	Double bit 3mm pin	screw-on	1 pc.
a)	255-9409.00-00000	RH version	Double bit 5mm pin	screw-on	1 pc.
a)	255-9410.00-00000	LH version	Double bit 5mm pin	screw-on	1 pc.
b)	255-9402.00-00000	RH / LH	Square 7mm	screw-on	1 pc.

	Product number	Version	Insert	Installation type	Delivery Unit
b)	255-9403.00-00000	RH / LH	Square 8mm	screw-on	1 pc.
c)	255-9405.00-00000	RH / LH	Triangular 8mm	screw-on	1 pc.

