

Flush-mounted Compression Latch L28/L37 Stainless Steel

7-086



Advantages

- Compression 6mm.
- Flush-mounted version.
- Indication of opened/closed position on the housing edge and the insert.
- Vibration-proof.
- IP69K to DIN EN 40050.
- RH / LH version.
- The H-dimension can be varied via the cranking of the cam.

Material

- **Housing, insert, axis, nut and anti-rotation device:** AISI 316
- **Serrated screw:** stainless steel
- **O-ring:** NBR

Remarks

(S) Door-thickness max. 13mm at GL 28mm

(S) Door-thickness max. 22mm at GL 37mm

(S) Door-thickness min. 1.8mm

Negatively bent cams can not be installed pre-assembled.

1. compression 6mm
2. o-ring
3. nut
4. anti-rotation device (included in scope of delivery)
5. washer when using cylinder head screws or weld studs/nuts

Flush-mounted Compression Latch with insert, RH version, closing left

	Product number	Insert	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	148-9102.00-00000	Square 8mm	28 mm	0 mm - 13 mm	screw-on	1 pc.
a)	148-9103.00-00000	Double bit 3mm pin	28 mm	0 mm - 13 mm	screw-on	1 pc.
a)	148-9107.00-00000	Triangular 8mm	28 mm	0 mm - 13 mm	screw-on	1 pc.
a)	148-9108.00-00000	Conical square 9mm	28 mm	0 mm - 13 mm	screw-on	1 pc.
b)	148-9302.00-00000	Square 8mm	37 mm	0 mm - 22 mm	screw-on	1 pc.
b)	148-9303.00-00000	Double bit 3mm pin	37 mm	0 mm - 22 mm	screw-on	1 pc.
b)	148-9307.00-00000	Triangular 8mm	37 mm	0 mm - 22 mm	screw-on	1 pc.
b)	148-9308.00-00000	Conical square 9mm	37 mm	0 mm - 22 mm	screw-on	1 pc.

Flush-mounted Compression Latch with insert, LH version, closing right

	Product number	Insert	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	148-9152.00-00000	Square 8mm	28 mm	0 mm - 13 mm	screw-on	1 pc.
a)	148-9153.00-00000	Double bit 3mm pin	28 mm	0 mm - 13 mm	screw-on	1 pc.
a)	148-9157.00-00000	Triangular 8mm	28 mm	0 mm - 13 mm	screw-on	1 pc.
a)	148-9158.00-00000	Conical square 9mm	28 mm	0 mm - 13 mm	screw-on	1 pc.
b)	148-9352.00-00000	Square 8mm	37 mm	0 mm - 22 mm	screw-on	1 pc.
b)	148-9353.00-00000	Double bit 3mm pin	37 mm	0 mm - 22 mm	screw-on	1 pc.
b)	148-9357.00-00000	Triangular 8mm	37 mm	0 mm - 22 mm	screw-on	1 pc.
b)	148-9358.00-00000	Conical square 9mm	37 mm	0 mm - 22 mm	screw-on	1 pc.

