

Quarter-Turn with L-Handle Pr20.1 L30/50 Stainless Steel

7-095.01



Advantages

- Quarter-turn with L-handle with extended housing.
- IP65 according to DIN EN 60529.
- RH / LH application.
- Grounding by single-sided grounding nut.
- Pre-assembled without cam.
- All lockable L-handles supplied with two keys.

Material

- **Handle:** AISI 316, satin polished
- **Housing, grounding nut and adapter:** stainless steel
- **Flat external seal:** NBR, black

Remarks

Please configure the quarter-turn with a cam.

For functional reasons, the cam must be assembled at 90° to the L-handle.

Price and delivery time on request.

Maximum door-thickness 20mm / 40mm.

Further housing lengths on request.

1. flat external seal

Quarter-Turn with L-handle

| | Product number | Housing length | Latching type | Door-thickness (S) | Installation type | Delivery Unit |
|----|-------------------|----------------|------------------------|--------------------|-------------------|---------------|
| a) | 100-9407.00-00000 | 30 mm | - | 0 mm - 20 mm | screw-on | 1 pc. |
| b) | 100-9408.00-00000 | 30 mm | keyed alike DIRAK 1333 | 0 mm - 20 mm | screw-on | 1 pc. |
| b) | 100-9409.00-00000 | 30 mm | keyed different | 0 mm - 20 mm | screw-on | 1 pc. |



| | Product number | Housing length | Latching type | Door-thickness (S) | Installation type | Delivery Unit |
|----|-------------------|----------------|------------------------|--------------------|-------------------|---------------|
| a) | 100-9410.00-00000 | 50 mm | - | 0 mm - 40 mm | screw-on | 1 pc. |
| b) | 100-9411.00-00000 | 50 mm | keyed alike DIRAK 1333 | 0 mm - 40 mm | screw-on | 1 pc. |
| b) | 100-9412.00-00000 | 50 mm | keyed different | 0 mm - 40 mm | screw-on | 1 pc. |

