

# Swinghandle RS 130 for Rod Latch

2-340



## Advantages

- Swinghandle can only be used with rod latches see product system 2-340.01
- For round rods with thread.
- PA version fully insulated.
- IP65 according to DIN EN 60529.
- RH / LH application.

## Material

- **Swinghandle:** PA, black or zinc die, black
- **Dish and cap:** PA, black

## Remarks

(S) Door-thickness max. 3mm

Dual cylinder RS130 see product system 2-126.02 (zinc die) and 2-126.04 (PA) on request.

Profile half cylinders and their assembly must be ordered separately.



## Swinghandle PA, black, for profile-cylinder, Ø46

	Product number	Latching type	Cylinder cover material	Securable	Installation type	Delivery Unit
a)	207-9056.00-00000	PHZ 40mm	-	-	screw-on	1 pc.
a1)	207-9057.00-00000	PHZ 40mm	PA	Yes	screw-on	1 pc.
a2)	207-9058.00-00000	PHZ 45mm	PA	Yes	screw-on	1 pc.

## Swinghandle, handle zinc die, dish PA black, for profile-cylinder, Ø46

	Product number	Latching type	Cylinder cover material	Securable	Installation type	Delivery Unit
a3)	207-9059.00-00000	PHZ 45mm	zinc die	Yes	screw-on	1 pc.

## Swinghandle PA, black, for profile-cylinder, □46

	Product number	Latching type	Cylinder cover material	Securable	Installation type	Delivery Unit
b)	207-9319.00-00000	PHZ 40mm	-	-	screw-on	1 pc.
b1)	207-9320.00-00000	PHZ 40mm	PA	Yes	screw-on	1 pc.
b2)	207-9321.00-00000	PHZ 45mm	PA	Yes	screw-on	1 pc.

## Swinghandle, handle zinc die, dish PA black, for profile-cylinder, □46

	Product number	Latching type	Cylinder cover material	Securable	Installation type	Delivery Unit
b2)	207-9322.00-00000	PHZ 45mm	zinc die	Yes	screw-on	1 pc.

