

# Concealed Hinge Pr03 120°

4-124



## Advantages

- For surface mounted doors.
- Hinge concealed.
- Door bending 23mm.
- RH / LH application.
- 120° Opening angle.
- Door-part weld-on.

## Material

- **Frame-part, pin and fastening washer:** steel, zinc plated
- **Door-part:** steel, untreated

## Remarks

1. installation instruction for fastening washer



## Concealed hinge

Product number	Frame-part	cutout in frame	Pin version	Delivery Unit
a) 243-9103.00-00000	with countersunk holes for M6	Ø6.3 or M6	without groove	10 pcs.
b) 243-9104.00-00000	with countersunk holes for M6	Ø6.3 or M6	with groove incl. locking washer DIN6799	10 pcs.

---

Product number	Frame-part	cutout in frame	Pin version	Delivery Unit
c) 243-9104.00-00001	with countersunk holes for M6	Ø6.3 or M6	with groove incl. o-ring	10 pcs.
d) 243-9101.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	without groove	10 pcs.
e) 243-9102.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	with groove incl. locking washer DIN6799	10 pcs.
f) 243-9102.00-00001	with countersunk holes for M6 + fastening washer	□8 or Ø10	with groove incl. o-ring	10 pcs.
g) 243-9109.00-00000	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	without groove	10 pcs.
h) 243-9110.00-00000	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	with groove incl. locking washer DIN6799	10 pcs.
i) 243-9110.00-00001	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	with groove incl. o-ring	10 pcs.

---

