

Concealed Hinge Pr03 120°

4-124.01









Advantages

- For surface mounted doors.
- Hinge concealed.
- Door bending 23mm.
- RH / LH application.
- 120° Opening angle.
- Door-part screw-on.

Material

• Frame- and door-part, pin and fastening washer: steel, zinc plated

Remarks

1. installation instruction for fastening washer



Concealed hinge

	Product number	Frame-part	cutout in frame	Pin version	Delivery Unit
a)	243-9107.00-00000	with countersunk holes for M6	Ø6.3 or M6	without groove	10 pcs.



Product number	Frame-part	cutout in frame	Pin version	Delivery Unit
b) 243-9108.00-00000	with countersunk holes for M6	Ø6.3 or M6	with groove incl. locking washer DIN6799	10 pcs.
c) 243-9108.00-00001	with countersunk holes for M6	Ø6.3 or M6	with groove incl. o-ring	10 pcs.
d) 243-9105.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	without groove	10 pcs.
e) 243-9106.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	with groove incl. locking washer DIN6799	10 pcs.
f) 243-9106.00-00001	with countersunk holes for M6 + fastening washer	□8 or Ø10	with groove incl. o-ring	10 pcs.
g) 243-9111.00-00000	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	without groove	10 pcs.
h) 243-9112.00-00000	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	with groove incl. locking washer DIN6799	10 pcs.
i) 243-9112.00-00001	with studs for M6 + fastening washer	Ø6.3, □8, Ø10	with groove incl. o-ring	10 pcs.



