

Concealed Hinge Pr03 120°

4-124.02



Advantages

- For surface mounted doors.
- Hinge concealed.
- Door bending 23 mm.
- RH / LH application.
- 120° Opening angle.
- Door-part screw-/weld-on.
- Captive pin due to securing clip.

Material

- **Frame- and door-part, pin and fastening washer:** steel, zinc plated
- **Securing clip:** POM, blue

Remarks

1. installation instruction for fastening washer
2. installation of securing clip and mounting of the door-part in the frame-part



Concealed hinge

Product number	Frame-part	cutout in frame	Surface door-part	Pin version	Delivery Unit
a) 243-9113.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	zinc plated	self-locking	10 pcs.
b) 243-9115.00-00000	with countersunk holes for M6	Ø6.3	zinc plated	self-locking	10 pcs.
c) 243-9114.00-00000	with studs for M6 + fastening washer	□8 or Ø10	zinc plated	self-locking	10 pcs.
d) 243-9116.00-00000	with studs for M6	Ø6.3	zinc plated	self-locking	10 pcs.
a) 243-9117.00-00000	with countersunk holes for M6 + fastening washer	□8 or Ø10	untreated	self-locking	10 pcs.
b) 243-9119.00-00000	with countersunk holes for M6	Ø6.3	untreated	self-locking	10 pcs.

Product number	Frame-part	cutout in frame	Surface door-part	Pin version	Delivery Unit
c) 243-9118.00-00000	with studs for M6 + fastening washer	□8 or Ø10	untreated	self-locking	10 pcs.
d) 243-9120.00-00000	with studs for M6	Ø6.3	untreated	self-locking	10 pcs.

