

DST Hinge Pr05 180°

4-152DST



Advantages

- Hinge with DIRAK-SNAP-Technology.
- For surface mounted doors for single cabinets.
- Hinge partly visible.
- Door bending 20mm.
- RH / LH application.
- 180° Opening angle.
- Lift-off.
- Installation of the frame-part by simple tool-less push into the cutout.
- IP65 according to DIN EN 60529 (optional).

Material

- **Frame- and door-part:** zinc die, matte black
- **Pin:** steel, zinc plated, AISI 304 or POM
- **Snap wedges:** sintered steel, zinc plated

Remarks

For light applications only!

Hinge

	Product number	Clamping range (S)	Material pin	Pin length L	Pin version	Installation type	Delivery Unit
a)	412-9059.00-01217	1.2 mm - 1.7 mm	steel, zinc plated	43 mm	loose	tool-less	10 pcs.
a)	412-9059.00-01722	1.7 mm - 2.2 mm	steel, zinc plated	43 mm	loose	tool-less	10 pcs.
b)	412-9060.00-01217	1.2 mm - 1.7 mm	AISI 304	43 mm	loose	tool-less	10 pcs.
b)	412-9060.00-01722	1.7 mm - 2.2 mm	AISI 304	43 mm	loose	tool-less	10 pcs.
c)	412-9061.00-01217	1.2 mm - 1.7 mm	POM	57 mm	self-locking	tool-less	10 pcs.
c)	412-9061.00-01722	1.7 mm - 2.2 mm	POM	57 mm	self-locking	tool-less	10 pcs.

