

Hinge Pr05 180°

4-161



Advantages

- 180° hinge for surface mounted doors for adjacent cabinets.
- RH / LH application.
- Door-bending 20mm.
- 180° opening angle.



Material

- **Frame- and door-part:** zinc die, glossy chrome plated or black
- **Washer:** brass, nickel plated
- **Pin:** steel, zinc plated or POM, natural

Remarks

1. pin steel, zinc plated
2. pin POM

Hinge, zinc die

Product number	Door-thickness (S)	Surface	Version	Material pin	Pin version	Installation type	Delivery Unit
a) 212-9025.00-00000	1.5 mm - 2 mm	glossy chrome plated	with M6 threaded stubs	steel	loose	screw-on	10 pcs.
b) 212-9026.00-00000	1.5 mm - 2 mm	glossy chrome plated	with countersunk holes for 6mm	steel	loose	screw-on	10 pcs.
a) 212-9033.00-00000	1.5 mm - 2 mm	glossy chrome plated	with M6 threaded stubs	POM	self-locking	screw-on	10 pcs.
b) 212-9034.00-00000	1.5 mm - 2 mm	glossy chrome plated	with countersunk holes for 6mm	POM	self-locking	screw-on	10 pcs.
a) 212-9027.00-00000	1.5 mm - 2 mm	black	with M6 threaded stubs	steel	loose	screw-on	10 pcs.
b) 212-9028.00-00000	1.5 mm - 2 mm	black	with countersunk holes for 6mm	steel	loose	screw-on	10 pcs.
a) 212-9035.00-00000	1.5 mm - 2 mm	black	with M6 threaded stubs	POM	self-locking	screw-on	10 pcs.
b) 212-9036.00-00000	1.5 mm - 2 mm	black	with countersunk holes for 6mm	POM	self-locking	screw-on	10 pcs.
a) 212-9527.00-00000	2.5 mm - 3.2 mm	black	with M6 threaded stubs	steel	loose	screw-on	10 pcs.
b) 212-9528.00-00000	2.5 mm - 3.2 mm	black	with countersunk holes for 6mm	steel	loose	screw-on	10 pcs.
a) 212-9535.00-00000	2.5 mm - 3.2 mm	black	with M6 threaded stubs	POM	self-locking	screw-on	10 pcs.
b) 212-9536.00-00000	2.5 mm - 3.2 mm	black	with countersunk holes for 6mm	POM	self-locking	screw-on	10 pcs.

