

DST Hinge Pr05 180°

4-184.01DST



Advantages

- For surface mounted doors for adjacent cabinets.
- Hinge partly-concealed.
- Door bending 20mm.
- RH and LH version.
- 180° opening angle.
- Tool-less installation of frame- and door-part.
- Door can be lifted-off at 30° opening angle.
- Lift-off safety, the door can't be lifted-off in closed position.
- IP65 according to DIN EN 60529 by flat external seal (optional).

Material

- **Frame- and door-part:** zinc die, black
- **Snap wedges:** sintered steel
- **Pin and spring:** stainless steel
- **Washer:** brass, nickel plated
- **Plug:** NBR, black

Remarks

For uninstallation (1.) of the frame-part remove plug (2.). Frame-part can be disengaged from outside with a screw driver.

Possible notching in the door for a gap of approx. 1-2mm between door and frame.

Attention: If you use the external seal (only necessary for the frame part), please order a larger clamping range.

Hinge

Product number	Version	Clamping range frame-part (S)	Clamping range door-part (S)	Pin version	Installation type	Delivery Unit
412-9008.00-01515	RH version	1.4 mm - 1.7 mm	1.3 mm - 2 mm	pressed in	tool-less	10 pcs.
412-9008.00-02020	RH version	1.8 mm - 2.1 mm	1.8 mm - 2.5 mm	pressed in	tool-less	10 pcs.
412-9008.00-02523	RH version	2.2 mm - 2.5 mm	2.3 mm - 3 mm	pressed in	tool-less	10 pcs.
412-9008.00-03030	RH version	2.8 mm - 3.1 mm	2.8 mm - 3.5 mm	pressed in	tool-less	10 pcs.
412-9009.00-01515	LH version	1.4 mm - 1.7 mm	1.3 mm - 2 mm	pressed in	tool-less	10 pcs.
412-9009.00-02020	LH version	1.8 mm - 2.1 mm	1.8 mm - 2.5 mm	pressed in	tool-less	10 pcs.
412-9009.00-02523	LH version	2.2 mm - 2.5 mm	2.3 mm - 3 mm	pressed in	tool-less	10 pcs.

Product number	Version	Clamping range frame-part (S)	Clamping range door-part (S)	Pin version	Installation type	Delivery Unit
412-9009.00-03030	LH version	2.8 mm - 3.1 mm	2.8 mm - 3.5 mm	pressed in	tool-less	10 pcs.

