

DST Hinge Pr05 180°

4-184.05DST



Advantages

- For surface mounted doors for adjacent cabinets.
- Hinge partly-concealed.
- Door bending 25mm.
- RH and LH version.
- 180° opening angle.
- Tool-less installation of door-part.
- Door can be lifted-off at 30° opening angle.
- Lift-off safety, the door can't be lifted-off in closed position.



Material

Door-part: zinc die, black

Frame-part: steel, black

Snap wedges: sintered steel

Pin and spring: stainless steel

Washer: brass, nickel plated

Remarks

Possible notching in the door for a gap of approx. 1-2mm between door and frame.

Hinge

Product number	Version	Clamping range door-part (S)	Pin version	Installation type	Delivery Unit
412-9016.00-00015	RH version	1.3 mm - 2 mm	pressed in	tool-less / screw-on	10 pcs.
412-9016.00-00020	RH version	1.8 mm - 2.5 mm	pressed in	tool-less / screw-on	10 pcs.
412-9016.00-00025	RH version	2.3 mm - 3 mm	pressed in	tool-less / screw-on	10 pcs.
412-9016.00-00030	RH version	2.8 mm - 3.5 mm	pressed in	tool-less / screw-on	10 pcs.
412-9017.00-00015	LH version	1.3 mm - 2 mm	pressed in	tool-less / screw-on	10 pcs.
412-9017.00-00020	LH version	1.8 mm - 2.5 mm	pressed in	tool-less / screw-on	10 pcs.
412-9017.00-00025	LH version	2.3 mm - 3 mm	pressed in	tool-less / screw-on	10 pcs.

Product number	Version	Clamping range door-part (S)	Pin version	Installation type	Delivery Unit
412-9017.00-00030	LH version	2.8 mm - 3.5 mm	pressed in	tool-less / screw-on	10 pcs.

