

DST Hinge 40x40 Pr01 180°

4-250DST



Advantages

- Hinge with DIRAK-SNAP-Technology.
- For nested doors.
- Hinge visible.
- RH / LH application.
- 180° Opening angle.
- Installation tool-less or tool-less / screw-on.

Material

- **Hinge halves:** zinc die, black
- **Pin:** stainless steel
- **Snap wedges:** sintered steel, zinc plated

Remarks

Other data and dimensions see product system 4-250.

Hinge

| | Product number | Version | Clamping range (S) | Pin version | Installation type | Delivery Unit |
|----|-------------------|--------------------------------------|--------------------|-------------|----------------------|---------------|
| a) | 418-9001.00-00015 | clip-in | 1.2 mm - 1.7 mm | pressed in | tool-less | 10 pcs. |
| a) | 418-9001.00-00020 | clip-in | 1.7 mm - 2.2 mm | pressed in | tool-less | 10 pcs. |
| a) | 418-9001.00-00025 | clip-in | 2.2 mm - 2.7 mm | pressed in | tool-less | 10 pcs. |
| a) | 418-9001.00-00030 | clip-in | 2.7 mm - 3.2 mm | pressed in | tool-less | 10 pcs. |
| b) | 418-9002.00-00015 | with molded in countersunk screws M5 | 1.2 mm - 1.7 mm | pressed in | tool-less / screw-on | 10 pcs. |
| b) | 418-9002.00-00020 | with molded in countersunk screws M5 | 1.7 mm - 2.2 mm | pressed in | tool-less / screw-on | 10 pcs. |
| b) | 418-9002.00-00025 | with molded in countersunk screws M5 | 2.2 mm - 2.7 mm | pressed in | tool-less / screw-on | 10 pcs. |
| b) | 418-9002.00-00030 | with molded in countersunk screws M5 | 2.7 mm - 3.2 mm | pressed in | tool-less / screw-on | 10 pcs. |
| c) | 418-9003.00-00015 | with countersunk holes for M5 | 1.2 mm - 1.7 mm | pressed in | tool-less / screw-on | 10 pcs. |
| c) | 418-9003.00-00020 | with countersunk holes for M5 | 1.7 mm - 2.2 mm | pressed in | tool-less / screw-on | 10 pcs. |
| c) | 418-9003.00-00025 | with countersunk holes for M5 | 2.2 mm - 2.7 mm | pressed in | tool-less / screw-on | 10 pcs. |

| | Product number | Version | Clamping range (S) | Pin version | Installation type | Delivery Unit |
|----|-------------------|-------------------------------|--------------------|-------------|----------------------|---------------|
| c) | 418-9003.00-00030 | with countersunk holes for M5 | 2.7 mm - 3.2 mm | pressed in | tool-less / screw-on | 10 pcs. |

