

DST Hinge 50x50 Pr01 180°

4-260DST



Advantages

- Hinge with DIRAK-SNAP-Technology.
- For nested doors.
- Hinge visible.
- RH / LH application.
- 180° Opening angle.
- Installation tool-less or tool-less / screw-on.
- Seismic-proof according to GR-63-CORE, Issue 4.



Material

- **Hinge halves:** zinc die, black
- **Pin:** stainless steel
- **Pin molded in:** steel, zinc plated
- **Snap wedges:** sintered metal, coated

Remarks

Other data and dimensions see product system 4-260.

Hinge

	Product number	Version	Clamping range (S)	Pin version	Installation type	Delivery Unit
a)	418-9101.00-00015	clip-in	1.2 mm - 1.7 mm	pressed in	tool-less	10 pcs.
a)	418-9101.00-00020	clip-in	1.7 mm - 2.2 mm	pressed in	tool-less	10 pcs.
a)	418-9101.00-00025	clip-in	2.2 mm - 2.7 mm	pressed in	tool-less	10 pcs.
a)	418-9101.00-00030	clip-in	2.7 mm - 3.2 mm	pressed in	tool-less	10 pcs.
b)	418-9104.00-00015	with molded in screws M6	1.2 mm - 1.7 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9104.00-00020	with molded in screws M6	1.7 mm - 2.2 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9104.00-00025	with molded in screws M6	2.2 mm - 2.7 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9104.00-00030	with molded in screws M6	2.7 mm - 3.2 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9106.00-00015	with countersunk holes for M6	1.2 mm - 1.7 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9106.00-00020	with countersunk holes for M6	1.7 mm - 2.2 mm	pressed in	tool-less / screw-on	10 pcs.

	Product number	Version	Clamping range (S)	Pin version	Installation type	Delivery Unit
c)	418-9106.00-00025	with countersunk holes for M6	2.2 mm - 2.7 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9106.00-00030	with countersunk holes for M6	2.7 mm - 3.2 mm	pressed in	tool-less / screw-on	10 pcs.

