

DST 3D Hinge, adjustable Pr01 180°

4-350DST



Advantages

- 3D hinge with DIRAK-SNAP-Technology.
- Adjustable in: height $\pm 2\text{mm}$ / width $\pm 2\text{mm}$ / depth $\pm 2\text{mm}$.
- For nested doors.
- Hinge visible.
- 180° Opening angle.
- RH and LH version.
- The installation of the frame part is tool-less, achieved by a simple push into the appropriate cutouts.

Material

- **Frame- and door-part:** zinc die, black
- **Base-plate:** steel, zinc plated
- **Pin:** brass, untreated, stainless steel on request
- **Snap wedges:** sintered metal, coated
- **Bushings:** PA, natural
- **Studs, bearing washer and c-clips:** stainless steel

Remarks

1. pushing screw for depth adjusting
2. securing screw for adjustable brass pin
3. PA bushing
4. base plate has 4 holes $\varnothing 4.1$ for possible additional fastening at the door.

3D hinge

Product number	Clamping range (S)	Version	Pin version	Installation type	Delivery Unit
417-9002.00-00015	1.2 mm - 1.7 mm	RH version	screwed	tool-less / screw-on	10 pcs.
417-9002.00-00020	1.7 mm - 2.2 mm	RH version	screwed	tool-less / screw-on	10 pcs.
417-9002.00-00025	2.2 mm - 2.7 mm	RH version	screwed	tool-less / screw-on	10 pcs.
417-9002.00-00030	2.7 mm - 3.2 mm	RH version	screwed	tool-less / screw-on	10 pcs.

Product number	Clamping range (S)	Version	Pin version	Installation type	Delivery Unit
417-9003.00-00015	1.2 mm - 1.7 mm	LH version	screwed	tool-less / screw-on	10 pcs.
417-9003.00-00020	1.7 mm - 2.2 mm	LH version	screwed	tool-less / screw-on	10 pcs.
417-9003.00-00025	2.2 mm - 2.7 mm	LH version	screwed	tool-less / screw-on	10 pcs.
417-9003.00-00030	2.7 mm - 3.2 mm	LH version	screwed	tool-less / screw-on	10 pcs.

