

DST Fastener 8x15

1-040DST



Advantages

- With DIRAK-SNAP-Technology for joining metal sheets.
- For cutout 8x15.
- Vibration-proof.
- Tool-less installation.
- The joining of metal sheets is achieved by pressing the fastener into the cutouts.
- With tool Part-No.: 292-0302.70 this fastener can be disconnected both from inside (after removal of the red plug) and from the outside.
- The tool is captive in the open position.

Material

- **Housing:** PA, black or light grey, RAL 7035
- **Snap wedges:** Grivory, black

Remarks

1. installation
2. disassembly
3. disassemble red plug

The dimension (S) always means the thickness of both sheets e.g.:

$$1.5 + 1.5 = 3$$

$$2.0 + 1.0 = 3$$

$$2.0 + 2.0 = 4$$

Fastener, PA

| Product number | Surface | Clamping range (S) | Installation type | Delivery Unit |
|-------------------|---------|--------------------|-------------------|---------------|
| 294-9001.00-00015 | black | 1.5 mm - 1.8 mm | tool-less | 10 pcs. |
| 294-9001.00-00020 | black | 2 mm - 2.3 mm | tool-less | 10 pcs. |
| 294-9001.00-00030 | black | 3 mm - 3.3 mm | tool-less | 10 pcs. |

| Product number | Surface | Clamping range (S) | Installation type | Delivery Unit |
|-------------------|---------------------|--------------------|-------------------|---------------|
| 294-9001.00-00040 | black | 4 mm - 4.3 mm | tool-less | 10 pcs. |
| 294-9002.00-00015 | light grey RAL 7035 | 1.5 mm - 1.8 mm | tool-less | 10 pcs. |
| 294-9002.00-00020 | light grey RAL 7035 | 2 mm - 2.3 mm | tool-less | 10 pcs. |
| 294-9002.00-00030 | light grey RAL 7035 | 3 mm - 3.3 mm | tool-less | 10 pcs. |
| 294-9002.00-00040 | light grey RAL 7035 | 4 mm - 4.3 mm | tool-less | 10 pcs. |

