

# DST Fastener □9.5

1-041.03DST



## Advantages

- With DIRAK-SNAP-Technology for joining of metal sheets.
- For cutout □9.5.
- Vibration-proof.
- Tool-less installation.
- This fastener can be disengaged from the front of the panel using a flathead screwdriver (Size max. 7x1mm, min. 6x1mm).
- The joining of metal sheets is achieved by pressing the fastener into the cutouts.

## Material

- **Housing:** zinc die, untreated
- **SNAP wedges:** sintered steel, zinc plated
- **Leaf spring:** stainless steel

## Remarks

**Removal:** by turning the screwdriver clockwise, the SNAP wedges (2.) are retracted. **a):** The fastener can be pressed manually from the back of the sheet. **b):** The leaf spring (1.) pushes the fastener out of the rear panel. (3.) Cutout in the rear panel can also be an ablong hole for tolerance adjustment. (4.) Cutout front panel. The (S) dimension indicates the total thickness of the sheet metal panels.

## Fastener with slotted insert

	Product number	Version	Clamping range (S)	Installation type	Delivery Unit
a)	294-9117.00-00022	without leaf spring	2 mm - 2.5 mm	tool-less	10 pcs.
a)	294-9117.00-00031	without leaf spring	3 mm - 3.3 mm	tool-less	10 pcs.
a)	294-9117.00-00035	without leaf spring	3.4 mm - 3.7 mm	tool-less	10 pcs.
a)	294-9117.00-00043	without leaf spring	4.2 mm - 4.5 mm	tool-less	10 pcs.
b)	294-9116.00-00017	with leaf spring	1.5 mm - 2 mm	tool-less	10 pcs.
b)	294-9116.00-00026	with leaf spring	2.5 mm - 2.8 mm	tool-less	10 pcs.
b)	294-9116.00-00030	with leaf spring	2.9 mm - 3.2 mm	tool-less	10 pcs.
b)	294-9116.00-00038	with leaf spring	3.7 mm - 4 mm	tool-less	10 pcs.

