

# Swinghandle FS PrC for Insert

3-150.03



## Advantages

- The locking cam is included.
- Version with cylinder cover is securable with wire padlock.
- IP65 according to DIN EN 60529 - version dish with cap.
- Dish with hook version is secured outside the sealed area.
- RH / LH application.
- Grounding by grounding clip (optional).

## Material

- **Swinghandle:** zinc die, chrome plated or black or PA, black
- **Dish:** PA, black

## Remarks

(S) Door-thickness 1.5 - 2.5mm

The swinghandles can be retrofitted with sliding cap product system 2-091.

Inserts and their assembly must be ordered separately.



## Swinghandle, dish PA, for insert

	Product number	Handle material	Surface handle	Dish	IP protection	Cylinder cover material	Installation type	Delivery Unit
a)	107-9247.00-00000	zinc die	chrome plated	with cap	IP65		screw-on	1 pc.
a)	107-9246.00-00000	zinc die	black	with cap	IP65		screw-on	1 pc.
b)	107-9251.00-00000	zinc die	chrome plated	with hook			screw-on	1 pc.
b)	107-9250.00-00000	zinc die	black	with hook			screw-on	1 pc.
a)	207-9270.00-00000	PA	black	with cap	IP65		screw-on	1 pc.
a)	207-9271.00-00000	PA	black	with cap	IP65	PA	screw-on	1 pc.
b)	207-9272.00-00000	PA	black	with hook			screw-on	1 pc.
b)	207-9273.00-00000	PA	black	with hook		PA	screw-on	1 pc.

