

DST Swinghandle FS PrC for PHZ

3-150DST



Advantages

- Swinghandle for profile-cylinder to DIN 18252.
- Tool-less installation.
- Installation with internal caps and o-ring for IP65 EN 60529 (seals are included).
- The swinghandle is symmetric and can be applied both for RH and LH doors.
- The swinghandle pre-assembled by DIRAK is hooked into the cutout provided and then clipped into place in the upper area.
- The flat rods are placed into shown position and secured by the clip-on PA cover.

Material

- **Swinghandle and dish:** PA, black
- **Snap wedges and pinion:** sintered steel

Remarks

Suitable flat rods see product system 3-171DST.

1. stroke 24mm
2. clearance height
3. hook-in the lower part and snap-in the swinghandle
4. LH, clockwise opening door
5. RH, counterclockwise opening door
6. clip cover

Profile half cylinders and their assembly must be ordered separately.

Swinghandle PA for PHZ 40mm

	Product number	Clamping range (S)	Dish	IP protection	Cylinder cover	Installation type	Delivery Unit
a)	407-9501.00-00015	1.3 mm - 2 mm	with hook and cap	IP65	-	tool-less	1 pc.
a)	407-9501.00-00018	1.5 mm - 2.2 mm	with hook and cap	IP65	-	tool-less	1 pc.

	Product number	Clamping range (S)	Dish	IP protection	Cylinder cover	Installation type	Delivery Unit
a)	407-9501.00-00020	1.8 mm - 2.5 mm	with hook and cap	IP65	-	tool-less	1 pc.
a1)	407-9502.00-00015	1.3 mm - 2 mm	with hook and cap	IP65	Yes	tool-less	1 pc.
a1)	407-9502.00-00018	1.5 mm - 2.2 mm	with hook and cap	IP65	Yes	tool-less	1 pc.
a1)	407-9502.00-00020	1.8 mm - 2.5 mm	with hook and cap	IP65	Yes	tool-less	1 pc.
b)	407-9504.00-00015	1.3 mm - 2 mm	with hook		-	tool-less	1 pc.
b)	407-9504.00-00018	1.5 mm - 2.2 mm	with hook		-	tool-less	1 pc.
b)	407-9504.00-00020	1.8 mm - 2.5 mm	with hook		-	tool-less	1 pc.
b1)	407-9503.00-00015	1.3 mm - 2 mm	with hook		Yes	tool-less	1 pc.
b1)	407-9503.00-00018	1.5 mm - 2.2 mm	with hook		Yes	tool-less	1 pc.
b1)	407-9503.00-00020	1.8 mm - 2.5 mm	with hook		Yes	tool-less	1 pc.

