

Compression Rod Latch RS / FS

3-211



Advantages

- For installation inside door sealing.
- Compression 4mm.
- Single or multi-point latching by using of additional latching devices.
- The connecting rods between the latching devices can be fixed easily in guides.
- For round rods Ø8mm or flat rods 3 x 14 mm.
- Oblong hole allows for installation adjustment.
- Seismic-proof according to GR-63-CORE, Issue 4.
- Vibration-proof according to DIN EN 61373.
- RH and LH version.
- Grounding by grounding clip (optional).

Material

- **Housing, driving rods, clamps, pinion:** zinc die

Remarks

Closing process:

1. a 90° turn of the swinghandle brings the cam into the locked position.
2. with another 45° turn the cam is pressed by 4mm against the clamping surface.

For reasons of strength and stability, DIRAK recommends the use of round bars.

Rod Latch with compression, 2 driving rods

	Product number	Version	Stroke	Installation type	Delivery Unit
a)	208-9076.00-00000	LH	23 mm	screw-on	1 pc.
a)	208-9077.00-00000	RH	23 mm	screw-on	1 pc.

Rod Latch with compression, 1 driving rod

	Product number	Version	Stroke	Installation type	Delivery Unit
b)	208-9078.00-00000	LH	23 mm	screw-on	1 pc.
c)	208-9079.00-00000	RH	23 mm	screw-on	1 pc.



