

# NT Swinghandle FS PrC Stainless Steel for PHZ

7-061















## Advantages

- Low profile swinghandle for profile-cylinder application with rod latch see product system 7-040.
- Protected against vandalism by extremly tight tolerances.
- The flush design prevents this swinghandle being used as climbing support.
- Locking cylinder fitted in the dish and protected against being forced through.
- Bolted internal cap is made of stainless steel.
- Fire protection tested with E60 classification according to DIN EN 45545-3.
- IP65 according to DIN EN 60529.
- RH / LH application.

#### Material

- Dish, handle, cover, cap, rotating disk and locking bolt: AISI 316
- Spring, pins and screws: stainless steel
- Cap sealing: NBR
- O-ring: NBR
- Washer: PTFE- Teflon

### Remarks

Door-thickness 1.5 - 2.5mm

- 1. open cover
- 2. turn key
- 3. the swinghandle springs open
- 4. turn handle

Optional cylinder cover screwable by M3x6, drive TX10.

Profile half cylinders and their assembly must be ordered separately.

## Swinghandle for profile cylinder, dish with cap

	Product number	Cylinder cover	Version	Installation type	Delivery Unit
a)	307-9301.00-00000	Yes	-	screw-on	1 pc.
b)	307-9306.00-00000	Yes	cover screw down	screw-on	1 pc.





