

# NT Swinghandle FS PrC Stainless Steel for PHZ

7-061



## Advantages

- Low profile swinghandle for profile-cylinder application with rod latch see product system 7-040.
- Protected against vandalism by extremely tight tolerances.
- The flush design prevents this swinghandle being used as climbing support.
- Locking cylinder fitted in the dish and protected against being forced through.
- Bolted internal cap is made of stainless steel.
- Fire protection tested with E60 classification according to DIN EN 45545-3.
- IP65 according to DIN EN 60529.
- RH / LH application.

## Material

- **Dish, handle, cover, cap, rotating disk and locking bolt** : AISI 316
- **Spring, pins and screws**: stainless steel
- **Cap sealing**: NBR
- **O-ring**: NBR
- **Washer**: PTFE- Teflon

## Remarks

Door-thickness 1.5 - 2.5mm

1. open cover
2. turn key
3. the swinghandle springs open
4. turn handle

Optional cylinder cover screwable by M3x6, drive TX10.

Profile half cylinders and their assembly must be ordered separately.

## Swinghandle for profile cylinder, dish with cap

	Product number	Cylinder cover	Version	Installation type	Delivery Unit
a)	307-9301.00-00000	Yes	-	screw-on	1 pc.
b)	307-9306.00-00000	Yes	cover screw down	screw-on	1 pc.

