

Pull and Lock Hook

1-250



Advantages

- Very suitable for applications on 19" racks and sliding doors.
- This device can be operated by all quarter-turns L18 with insert or handles.
- The extremely positive torque ratio allows for controlling this hook-latch by a cylinder latch.
- 90° stroke.
- Latching direction is always clockwise.
- Vibration-proof.

Material

- **Pull and lock hook, locking bolt, line-up fork:** steel, zinc plated

Remarks

(S) Door-thickness 1.5 - 2.5mm

1. open position.
2. hook catches behind the locking bolt and continuing the closing rotation, the hook is then being pulled automatically against the locking bolt. The pulling stroke is 5mm.
3. at the end of rotation process the hook has a vibration proof latch behind the locking bolt.



Pull and Lock Hook

| | Product number | Name | Compression | Vibration-proof | Installation type | Delivery Unit |
|----|-------------------|-------------------------------------|-------------|-----------------|-------------------|---------------|
| a) | 200-9602.00-00000 | Pull and Lock Hook | 5 mm | Yes | screw-on | 10 pcs. |
| b) | 200-3704.00-00000 | Locking bolt for Pull and Lock Hook | | No | weld-on | 10 pcs. |
| c) | 200-3703.00-00000 | Line-up fork for Pull and Lock Hook | | No | screw-on | 10 pcs. |



