

Flush Mounted Trap-Door Latch

6-1381

RoHS
WEEE



Advantages

- Flush mounted trap-door latch with integrated T-handle and safety insert.
- Vibration-proof design.
- T-handle with 95° opening angle.
- Width of T-handle 25mm.
- T-handle with rubber stop to prevent rattling.
- Encasement surface perfectly smooth to prevent dirt deposits.
- Mounted with fastening bracket with two M6 allen screws DIN EN ISO 4762.
- Cutout with anti-twist safeguard.
- Also available without locking device (only flush-mounted T-handle).

Material

- **Housing and T-handle:** zinc die, chrome plated
- b)
- **Insert:** AISI 303
- c)
- **Insert:** zinc die, chrome plated

Remarks

The door-thickness (S) amounts to max. 6mm with the screw provided M6x16.

1. fastening bracket
2. spring-loaded link
3. locking device for T-handle

Attention:

H-dimension of the L=35 cam $\geq 14\text{mm}$

H-dimension of the L=45 cam $\geq 14\text{mm}$

Only for use with cams part-no. 200-06XX and 200-04XX!

Trap-door latch

	Product number	Insert	Version	Installation type	Delivery Unit
a)	213-9401.00-00000	without	without Fixing bracket	screw-on	1 pc.
b)	213-9403.00-00000	Conical square 9mm	without Fixing bracket and without spring-loaded link	screw-on	1 pc.
c)	213-9402.00-00000	Square 8mm	with fixing bracket and cylinder head screws M6x16	screw-on	1 pc.



