

# Compression Lever Latch

6-160

RoHS  
WEEEDIN  
61373

## Advantages

- Flat compression lever latch with release button.
- With pre-assembled mounting bracket.
- No rear access needed for assembly.
- In closed position the lever latch cannot be disassembled.
- Vibration-proof according to DIN EN 61373.
- Adjustment of the H-dimension (1.) from 3 to 46mm.
- Lockable latches with stainless dust cap and 2 keys.
- Visibility of closing position by indicator at the insert variants (c.).



## Material

- **Compression lever latch:** zinc die, black, powder coated
- **Clamp:** steel, zinc plated
- **Insert:** zinc die, black, powder coated

## Remarks

(S) Door-thickness max. 3.2mm

Installation:

2. the complete latch can be installed in the cutout from the front.
3. by turning the screw (PH2) from the outside, the mounting bracket spreads and fixes the latch in the door panel.
4. the latch is securely fastened by the mounting bracket in the cutout.
5. by closing the latch the door is pulled against the frame.

## Compression Lever Latch, lockable

	Product number	variable H-dimension	Length lever arm	Latching type	Installation type	Delivery Unit
a)	282-9417.00-00000	3 mm - 24 mm	35 mm	keyed alike DIRAK 1333	screw-on	1 pc.
a)	282-9418.00-00000	3 mm - 24 mm	35 mm	keyed different	screw-on	1 pc.
a)	282-9420.00-00000	22 mm - 46 mm	57 mm	keyed alike DIRAK 1333	screw-on	1 pc.
a)	282-9421.00-00000	22 mm - 46 mm	57 mm	keyed different	screw-on	1 pc.

## Compression Lever Latch, without lock

	Product number	variable H-dimension	Length lever arm	Installation type	Delivery Unit
b)	282-9416.00-00000	3 mm - 24 mm	35 mm	screw-on	1 pc.
b)	282-9419.00-00000	22 mm - 46 mm	57 mm	screw-on	1 pc.

## Compression Lever Latch, with insert

	Product number	variable H-dimension	Length lever arm	Insert	Installation type	Delivery Unit
c)	282-9428.00-00001	3 mm - 24 mm	35 mm	Square 6mm	screw-on	1 pc.
c)	282-9428.00-00002	3 mm - 24 mm	35 mm	Square 7mm	screw-on	1 pc.
c)	282-9428.00-00003	3 mm - 24 mm	35 mm	Square 8mm	screw-on	1 pc.
c)	282-9428.00-00004	3 mm - 24 mm	35 mm	Triangular 7mm	screw-on	1 pc.
c)	282-9428.00-00005	3 mm - 24 mm	35 mm	Triangular 8mm	screw-on	1 pc.
c)	282-9428.00-00006	3 mm - 24 mm	35 mm	Double bit 3mm pin	screw-on	1 pc.
c)	282-9428.00-00007	3 mm - 24 mm	35 mm	Double bit 5mm pin	screw-on	1 pc.
c)	282-9428.00-00008	3 mm - 24 mm	35 mm	Slotted 2x4mm	screw-on	1 pc.
c)	282-9429.00-00001	22 mm - 46 mm	57 mm	Square 6mm	screw-on	1 pc.
c)	282-9429.00-00002	22 mm - 46 mm	57 mm	Square 7mm	screw-on	1 pc.
c)	282-9429.00-00003	22 mm - 46 mm	57 mm	Square 8mm	screw-on	1 pc.
c)	282-9429.00-00004	22 mm - 46 mm	57 mm	Triangular 7mm	screw-on	1 pc.
c)	282-9429.00-00005	22 mm - 46 mm	57 mm	Triangular 8mm	screw-on	1 pc.
c)	282-9429.00-00006	22 mm - 46 mm	57 mm	Double bit 3mm pin	screw-on	1 pc.
c)	282-9429.00-00007	22 mm - 46 mm	57 mm	Double bit 5mm pin	screw-on	1 pc.
c)	282-9429.00-00008	22 mm - 46 mm	57 mm	Slotted 2x4mm	screw-on	1 pc.

