

# DST Cam Catch

1-050DST



## Advantages

- Concealed cam catch.
- RH / LH application.
- Tool-less clip-in assembly into a 30 x 10mm cutout in the frame.
- Available in 2 different heights, 10 and 16mm.
- IP65 according to DIN EN 60529 (optional).

## Material

- **Cam catch:** zinc die, black
- **Snap wedges:** sintered steel

## Remarks



## Cam catch

	Product number	Clamping range (S)	Cam catch	Installation type	Delivery Unit
a)	408-9106.33-00010	0.7 mm - 1.2 mm	10mm	tool-less	10 pcs.
a)	408-9106.33-00015	1.2 mm - 1.7 mm	10mm	tool-less	10 pcs.
a)	408-9106.33-00020	1.7 mm - 2.2 mm	10mm	tool-less	10 pcs.
a)	408-9106.33-00025	2.2 mm - 2.7 mm	10mm	tool-less	10 pcs.
a)	408-9106.33-00030	2.7 mm - 3.2 mm	10mm	tool-less	10 pcs.
b)	408-9107.33-00010	0.7 mm - 1.2 mm	16mm	tool-less	10 pcs.
b)	408-9107.33-00015	1.2 mm - 1.7 mm	16mm	tool-less	10 pcs.
b)	408-9107.33-00020	1.7 mm - 2.2 mm	16mm	tool-less	10 pcs.
b)	408-9107.33-00025	2.2 mm - 2.7 mm	16mm	tool-less	10 pcs.
b)	408-9107.33-00030	2.7 mm - 3.2 mm	16mm	tool-less	10 pcs.

