

# Dust Caps and Sealing Plug Pr20.1

1-270



## Advantages

- **Dust caps** for head Ø28mm - Ø32mm.
- **Material TPU:** excellent resistance to pure mineral oils and greases.
- **Sealing plugs** for inner diameter Ø16.1mm and Ø18.1mm.
- IP protection according to DIN EN 60529.

## Material

- **Dust cap:** PP or TPU, black
- **Sealing plug:** NBR+PVC, black

## Remarks

When using the dust cap a) the H-dimension changes by 1.2mm.

When using the dust cap b), the H-dimension changes by 2.8mm. (The dust cap is equipped with sealing ribs (t=3.2mm) which are compressed to t=2.8mm with a tightening torque of 15Nm.)

The sealing plug c) is only for out-side triangular respectively square insert!

## Accessories Quarter-turn

Product number	Name	Diameter Ø	IP protection	Material	Temperature range	Delivery Unit
a) 200-4101.00-00000	Dust cap		IP65	PP	0° to +80°C	10 pcs.
b) 200-4103.00-00000	Dust cap		IP65/67	TPU	-40° to +100°C	10 pcs.
c) 292-0606.00-00000	Sealing plug	16.1 mm	IP65	NBR+PVC	-	10 pcs.
d) 292-0605.00-00000	Sealing plug	18.1 mm	IP65	NBR+PVC	-	10 pcs.

