

# 2-, 3- and 4-Point Cam Adapter

2-151



## Advantages

- 3-point cam adapter for cams of product system 1-102.
- With and without 90° stop.
- The raised rod stub is necessary for swinghandles, enabling the lower rod passing over the lower cap.
- 4-Point cam adapter: with additional linkage.
- For those applications, where beyond the standard control of 2 locking-rods, an additional rod can be used. E.g. controlling a switch or defeater-mechanism.



## Material

- **3-point cam adapter and 4-point cam adapter:** zinc die, zinc plated

## Remarks

Incl. 2 c-clips

**Note:** H-dimension of cam (C) increases by 4mm. E.g. cam 200-0418 results in an H-dimension of 22mm.

Please pay attention to the screw length: screw should enter at least 6mm.

1. with stop
2. without stop

## Adapter for 3-point cam

|    | Product number    | Stop | 2-point locking | 3-point locking | 4-point locking | Installation type | Delivery Unit |
|----|-------------------|------|-----------------|-----------------|-----------------|-------------------|---------------|
| a) | 200-9595.00-00000 | Yes  | Yes             | Yes             | Yes             | screw-on          | 1 pc.         |
| b) | 200-9596.00-00000 | Yes  | Yes             | Yes             | No              | screw-on          | 1 pc.         |
| c) | 207-9595.00-00000 | No   | Yes             | Yes             | Yes             | screw-on          | 1 pc.         |
| d) | 207-9596.00-00000 | No   | Yes             | Yes             | No              | screw-on          | 1 pc.         |

