

Profile-Cylinder Stainless Steel

7-069

RoHS
WEEEDIN EN
45545-3
(E60)

Advantages

- Profile-cylinder with insert for swinghandles see product system 7-060 and 7-066.
- 40mm length
- Spring loaded clip-in cam.
- Fire protection tested with E60 classification according to DIN EN 45545-3.

Material

- **Housing, cam and insert:** AISI 316

Remarks

i) security insert with free rotating 8mm triangular front part. The free rotating front part increases the security because the insert can only be opened with the suitable triangular key.

Profile-cylinder with insert

	Product number	Insert	Delivery Unit
a)	211-9226.00-00000	Square 6mm	1 pc.
b)	211-9227.00-00000	Square 7mm	1 pc.
c)	211-9228.00-00000	Square 8mm	1 pc.
d)	211-9229.00-00000	Triangular 7mm	1 pc.
e)	211-9230.00-00000	Triangular 8mm	1 pc.
f)	211-9231.00-00000	Double bit 3mm pin	1 pc.
g)	211-9232.00-00000	Double bit 5mm pin	1 pc.
h)	211-9233.00-00000	Slotted 2x4mm	1 pc.
i)	211-9242.00-00000	Security insert with free rotating 8mm triangular front part	1 pc.
j)	211-9238.00-00000	Conical square 9mm	1 pc.

