

# Leveling Foot M10/M12/M16/M20

6-009



## Advantages

- Length of hexagon head screw DIN 933/ISO 4017 freely selectable (e) or hex. nut, low form DIN 439/ISO 8675/ISO 4035.
- Inclination angle of +/- 25°.
- Large contact surface due to the use of a large ball in conjunction with a small plate diameter.
- No lifting forces because the ball is stored in an indentation. This prevents the edge on the plate from breaking.
- In relation to the load the plate can be designed smaller and thus be mounted closer to the edge of the housing.
- Anti-slip insert included.

## Material

- **Plate, sleeve and nut:** PA6
- **Anti-slip insert:** NBR

## Remarks

The values given in the table are based on a simple compressive load perpendicular to the Leveling Foot. The additional bending and buckling stresses that frequently occur in practice lead to reduced load-bearing capacity of the bolt and must be taken into account accordingly.

## Leveling foot

	Product number	Diameter Ø	Thread size	SW	Static load capacity in kN	Delivery Unit
a)	580-9014.00-00001	50 mm	M10	17 mm	15.5	20 pcs.
b)	580-9013.00-00001	50 mm	M12	19 mm	15.5	20 pcs.
c)	580-9011.00-00001	65 mm	M16	24 mm	34	8 pcs.
d)	580-9012.00-00001	83 mm	M20	30 mm	39	4 pcs.

**Supported by:**



**Federal Ministry  
for Economic Affairs  
and Energy**



**on the basis of a decision  
by the German Bundestag**

