

Compression Latch Pr20.1 L22/32 Stainless Steel

7-078



Advantages

- Compression 6mm.
- Flat head shape.
- The coloured marking on the casing top indicates the opened/closed position in form of a padlock.
- Insert with coloured marking.
- Vibration-proof.
- Fire protection tested with E60 classification according to DIN EN 45545-3.
- IP65/67 according to DIN EN 60529.
- IP69K according to DIN 40050.
- RH and LH version.
- Grounding by single-sided grounding nut.
- The H-dimension can be varied via the cranking of the cams.



Material

- **Housings, insert, axle and grounding nut:** AISI 316
- **Serrated screw:** AISI 304
- **O-ring:** NBR, black

Remarks

(S) Door-thickness max. 12mm for GL22

(S) Door-thickness max. 22mm for GL32

Please configure the quarter-turn with a cam.

Negatively bent cams can not be installed pre-assembled.

1. compression 6mm
2. single-sided griunding nut
3. flat external seal
4. GL 32mm with foamed sealing PUR

Compression Latch with insert, version RH, closing left

	Product number	Insert	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	248-9043.00-03008	Square 8mm	22 mm	0 mm - 12 mm	screw-on	1 pc.
a)	248-9043.00-06008	Triangular 8mm	22 mm	0 mm - 12 mm	screw-on	1 pc.

	Product number	Insert	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	248-9043.00-09003	Double bit 3mm pin	22 mm	0 mm - 12 mm	screw-on	1 pc.
a)	248-9043.00-07007	Conical square 9mm	22 mm	0 mm - 12 mm	screw-on	1 pc.
b)	248-9100.00-00000	Square 6mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9101.00-00000	Square 7mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9102.00-00000	Square 8mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9103.00-00000	Double bit 3mm pin	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9104.00-00000	Double bit 5mm pin	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9105.00-00000	Triangular 6.5mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9106.00-00000	Triangular 7mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9107.00-00000	Triangular 8mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9108.00-00000	Conical square 9mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9109.00-00000	Hex. SW 11	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9110.00-00000	konischer Dreikant spitz, 7mm	32 mm	0 mm - 22 mm	screw-on	1 pc.

Compression Latch with insert, version LH, closing right

	Product number	Insert	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	248-9042.00-03008	Square 8mm	22 mm	0 mm - 12 mm	screw-on	1 pc.
a)	248-9042.00-06008	Triangular 8mm	22 mm	0 mm - 12 mm	screw-on	1 pc.
a)	248-9042.00-09003	Double bit 3mm pin	22 mm	0 mm - 12 mm	screw-on	1 pc.
a)	248-9042.00-07007	Conical square 9mm	22 mm	0 mm - 12 mm	screw-on	1 pc.
b)	248-9150.00-00000	Square 6mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9151.00-00000	Square 7mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9152.00-00000	Square 8mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9153.00-00000	Double bit 3mm pin	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9154.00-00000	Double bit 5mm pin	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9155.00-00000	Triangular 6.5mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9156.00-00000	Triangular 7mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9157.00-00000	Triangular 8mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9158.00-00000	Conical square 9mm	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9159.00-00000	Hex. SW 11	32 mm	0 mm - 22 mm	screw-on	1 pc.
b)	248-9160.00-00000	konischer Dreikant spitz, 7mm	32 mm	0 mm - 22 mm	screw-on	1 pc.

